



Features water drop alarms with high sensitivity.

The on-site length can be freely cut

The connector can be installed on site by yourself, and the installation is convenient and simple

The strip must be dried for reset and can be reused.

Its ultra-thin design allows for customization to any length.



Product Overview

The GDL1 series flat liquid leakage detection tape is specially designed for detecting leakage and dripping of conductive liquids. It can be cut to the required length on site according to the demand, and connectors can also be made on site by oneself. It can make three-way connectors and straight-through connectors on site, and has strong compatibility. It can be used in conjunction with the GDL3100 leak detection controller. If the leakage detection tape detects liquid, it will trigger an alarm and output a signal. This leakage detection tape is designed by Superbo, which is lightweight, highly flexible, foldable and easy to install with double-sided tape to meet various needs.

Technical Specifications

Cable Material	PET + Alloy Wire
Core Resistance	13 ohms <100 meters
Cable Color	White
Cable Size	10mm wide, 0.2 mm thick, with a sensing interval of 25mm
Tensile Strength	20KG
Cable Weight	10g per meter
Maximum Exposure Temperature	85°C

Product Selection

Product Model	Description
GDL1	Connector not included
GDL1-3	3-meter leak detection cable, Included connector
GDL1-5	5-meter leak detection cable, Included connector
GDL1-()	Tailor the length and connector to your needs

For debugging software, user instructions, or communication protocols, please contact our sales staff.